BP11452

O.M.B. NO. 3067-0077 Expires May 31, 1996

ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

TENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR).

Instructions for completing this form can be found on the following pages.

otorrimie and proper meeter	Instructions for com	pleting this f	orm can be found on th	e following pag	ges.
SECTION A PROPERTY I			RMATION	D B B	FOR INSURANCE COMPANY USE
FUILDING OWNER'S NAME	TON				POLICY NUMBER
STREET ADDRESS (Including Ap	t., Unit, Suite and/or Bldg. N	umber) OR P.O. F	ROUTE AND BOX NUMBER	JAN	COMPANY NAIC NUMBER
3371 BAYOU		BOAT KEY,	, FLORIDA	Sim	0 1999
THER DESCRIPTION (Lot and E	Block Numbers, etc.)	11	No 2	BUILDING DE TOWN OF LONG	PARTA
LOT 28, BLOCK	"A", BAY ISI	ES, V411	140. 2	TOWN OF LONG STATE	BOAT KEY ZIP CODE
LONGBOAT KE				FLORIDA	34228
LUNGBUAT KE	SECTION B FL	OOD INSURA	NCE RATE MAP (FIRM)		
ovide the following from the			The state of the s		
	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION
1. COMMUNITY NUMBER	y us			A-13	(in AO Zones, use depth)
125126	0010	В	5/18/92		11
For Zones A or V, where	no BFE is provided or	n the FIRM, ar	nd the community has esta FIRM datum-see Section	ablished a BFE	Other (describe on back for this building site, indicate
	SECTIO	NC BUILDI	NG ELEVATION INFORM	NOITA	
the selected diagram, (c). FIRM Zone A (without below (check one) (d). FIRM Zone AO. The one) the highest grade level) elevated in according to the comments on Payments on Pa	is at an elevation of L. BFE). The floor used the highest grade action used as the reference adjacent to the build ordance with the commutum system used in decay.	d as the reference level from the le	deet NGVD (or other FIF) ince level from the selecter cuilding. In the selected diagram is didepth number is available color management ordinance above reference level elements and in measuring the	RM datum—see S d diagram is le, is the buildinger Yes evations: No elevations is diff	above or below (check g's lowest floor (reference No Unknown 229 Other (describe ferent than that used on
the FIRM [see Section equation under Comme	B, Item 7], then conve nts on Page 2.)	ert the elevation	ons to the datum system u	ised on the FIKI	M and show the conversion
. Elevation reference mar					
case this certificate will of will be required once con	ction drawings is only only be valid for the bu astruction is complete.	valid if the bui ilding during t)	ilding does not yet have the course of construction.	e reference leve A post-constru	iction Elevation Certificate
The elevation of the low Section B, Item 7).	est grade immediately	adjacent to the	he building is:	J. ☑ .feet NGVI	O (or other FIRM datum-see
1	S	ECTION D C	OMMUNITY INFORMATI	ON	en mer in the entire
If the community official is not the "lowest floor" floor" as defined by the 2. Date of the start of constant is a second of the start of constant is a second of the start of constant is a second of the start	as defined in the como ordinance is:	munity's flood; feet	olain management ordinar NGVD (or other FIRM da	nce, the elevation	indicated in Section C, Item 1 in of the building's "lowest n B, Item 7).

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LICENSE NUMBER (or Affix Seal) DENHIS HOOVER 4419 COMPANY NAME TITLE REGISTOREO BISHOP \$ ASSOCIATE **ADDRESS** CITY 78 SAKASOTA +60UDA SIGNATURE DATE PHONE 813 11/22/94 Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner:

COMMENTS: ENTERINCE foyer timisher FLOOR ElOVATION

ON WITH ON PILES BASEMENT SLAB PIERS, OR COLUMNS **ZONES** ZONES ZONES REFERENCE LEVEL REFERENCE LEVEL FLOOD ADJACENT REFERENCE FLOOD LEVEL **ELEVATION** REFERENCE **ADJACENT** ADJACENT

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.