ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

OMB 3067-007 EXPIRES: JUNE 30 1990

This form is to be used for: 1) Post-FIRM construction only when the base flood information is available for the building site; and 2) Pre-FIRM buildings rated using Post-FIRM rules.

Instruc	ions for completing this form can be found on	the reverse side.	्यसाध्य मध्य कार्य	गांजाल छन्।
Lou Zarkovacki	uran e Application-Prin 2 Volu	na na Rod Insi	POLICY NUMBER	1.000-7 +d? -
BUILDING OWNER'S NAME			POLICI NOMBER	
4138 Gulf of Mexico Drive	eoled, by construction techniques	the 'grade unaff	as bánisi si so	ang tanàna kiti
AptA/Unit-U Suite-S/BldgB	NO. CALENCE AND	ROUTE	BO	X NUMBER
Unit No. 1, The Embassy		(with 8PE) Line	A bas MA .3A 0	A-IL and The
OTHER DESCRIPTION (Block and lot numbers., etc.)	nov in analysis a planta of the second s	in isvai egosiaria la stil txil estudi	and an analysis and	nverit entre
Longboat Key		".nooff toval aons	Florida	34228
CITY	op at here." Prain the Fleed Blist ran out-at		STATE	ZIP CODE
This form is to be completed by a land surveyor, eng. information for zones A1-A30, AE, AH, A(with BFE), V owner, or the owner's representative should complete authorized by local law or ordinance to provide filodop	1-V30, VE, and V(with BFE) is required the information in Section I and may a lain management information may also	d. In the case of zon also complete the ce o complete this form.	e AO, the buildina off	icial, the property
SECTION	ON I BUILDING ELEVATION IN	NFORMATION	rformed blocks one	House the t
 Using the Flood Insurance Manual or the NFIF FIRM Zones A1-A30, AE, AH, and A (with BF elevation of <u>16.03</u> feet NGVD. (or othe 3. FIRM Zones V1-V30, VE, and V (with BFE). The selected diagram is at an elevation of 	E). The top of the reference level er datum-see #5) The bottom of the lowest horizonta feet NGVD (or other datum-	floor from the sele I structural membe see #5).	ected diagram is at er of the reference	an Ievel floor from
4. FIRM Zone AO. The floor used as the reference the building (also enter in line 8). This value flood depth number is available, is the building floodplain management ordinances? Yes	must be equal to or greater than t ng's lowest floor (or reference leve s	he AO Zone flood I) elevated in acco	depth number liste rdance with the co	ed below. If no mmunity's
5. Indicate the elevation datum system used in				
6. Indicate the elevation datum system used on				Carrier Carrier
(ATTENTION: If the elevation datum used in m must be converted to the datum system used of	easuring the elevations is different that on the FIRM.)	n that used on the F	IRM, then the elevation	ons provided
 * A "No" answer is only valid if the building tion drawings and do not complete question construction. After construction of the reference continued flood insurance coverage. 8. Provide the following measurements using the a. The reference level is: 10 feet above below (check one) 	 #8. If "No" is checked, this certilence level floor is completed, a pose of the second second	fication will be vali st-construction ele g (round to the ne age floor (if applic et X abovet	d only for buildings vation certificate w arest foot).	s in the course o ill be required fo he highest grade
SECTION II	FLOOD INSURANCE RATE M		COLUMN THE PARTY OF	
		the second framework in the second		an a
Provide the following from the proper FIRM (see				
COMMUNITY NO. PANEL NO. SUFFIX 125126 00055 B		BASE FLOOD ELEV. A A0 Zone, use depth) 12	COMMUNITY ESTIM ELEVATION ESTABLI OR ZONE V, IF	SHED FOR ZONE A
Elevation reference mark used appears on FIRI	M Yes X No (See reverse sid	de for details)		<u></u>
	SECTION III CERTIFICATIO			
This certification is to be signed by a land surveyor, a elevation information for zones A1-A30, AE, AH, A(wi property owner, or the owner's representative can sig floodplain management information, may also sign th the data available. I understand that any false statem	n the certification. Community officials e certification. I certify that the informat	who are authorized tion on this certificate	by local law or ordina e represents my best	nce to provide efforts to interpret
Lawrence R. Weber		PLS 386		
CERTIFIER'S NAME President		ENSE NUMBER (or Affin		20
	Weber Engine	cring a su	rveying, 1	nc.
3932 Swift Road Swite A	Sarasota	F1	orida	34231
address hurrence hurren	er April	19, 1990 (STATE 813) 921-3	^{ZIP} 914
SIGNATURE	in al sonorbia són àsant à la que d'au	DATE	PHONE	EN OT TOWN
The insurance agent should attach the original copy of policyholder and the third copy retain	ned by the agent. The fourth copy is for th	e local community per	e second copy should b mit office, if required.	e supplied to the
FOR OPTIONAL COMMUNITY USE: Is the reference	THIS FORM MAY BE REPRODUCED	•		

ELEVATION CERTIFICATE

INSTRUCTIONS FOR COMPLETING THE ELEVATION CERTIFICATE

The Flood Insurance Manual and the Flood Insurance Application—Part 2 Worksheet contains a series of diagrams that of are to be used to determine the reference level for the specific structure in question. The diagrams are available through local insurance agents or the National Flood Insurance Program.

"Natural grade" is defined as the "grade unaffected by construction techniques such as fill, landscaping, or berming."

A reference level is shown in each of the worksheet diagrams of the various building types. For property locations in neuronal zones A1-A30, AE, AH, and A (with BFE), Line 2 of the Elevation Certificate indicates that the elevation should be measured from the top of the reference level floor. For property locations in zones V1-V30, VE, and V (with BFE), Line 3 of the Elevation Certificate indicates that the elevation should be measured from the bottom of the lowest horizontal structural member of the reference level floor.*

* The insured will determine the measurements using the "top of floor" from the Flood Insurance-Part 2 Worksheet diagrams.

COLUMN TWO IS NOT	The diagram, right, demonstrates	WITH BASEMENT	<mark>by a land surreyor</mark> AE, AH, Avarib Ei ortanya should tha	ON PIERS	d form is lo amation ior nercr. the o	
	the differences between the point A v	ZONES	ZONES	ZONES	REFERENCE	
	that elevations should be measured ZONES ZONES ZONES				LEVEL	
the second se	Elevations for all A zones should be measured from the top of the reference level floor.				ever lo mineres	
10000	Elevations for all V zones should BASE FLOOD be measured from the bottom of ELEVATION the lowest horizontal structural member of the reference			NATURAL GRADE	BASE FLOOD ELEVATION	
A Second Se		N OF REFERENCE				

The reference level elevation may be reported to the same level of precision used to report base flood elevation on the FIRM (e.g., if the base flood elevation is shown to the nearest half foot, the reference level may be reported to the nearest half foot).

Base flood elevations are shown on the community's Flood Insurance Rate Map (FIRM) for zones A1-A30, AH, AE, V1-V30, and VE. Base flood elevations may also be on file with the community for zones A and V for all subdivisions and other new developments greater than 50 lots or 5 acres, whichever is the lesser, if the start of construction was after December 31, 1974.

Base flood depth numbers are shown on the community's Flood Insurance Rate Map (FIRM) for zone AO. These depth numbers should be used to compare with the height of the reference level floor above highest natural grade in Line 8 of the Elevation Certificate.

Elevation reference marks other than those shown on the FIRM may be used for reference level elevation determinations. In areas experiencing ground subsidence, the most recently adjusted reference mark elevations available must be used for elevation determinations. If a reference mark not shown on the FIRM is used, identify the reference mark used in the comment section.

Date of FIRM used in Section II of the Elevation Certificate can be either the date of the FIRM in effect when the certification is being provided or the date of the FIRM that was in effect at the time the building was constructed.

COMMENTS:

Surveying, Inc.

NOTE TO INSURANCE AGENTS AND COMMUNITY OFFICIALS: In all A zones, the reference level is the top of the lowest floor and in V zones the reference level is the bottom of the slab/horizontal support. Agents should refer to the flood insurance manual for instruction on lowest floor definition.

Weber Engineering

C.