PERMUZ # BP 14181

ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR INSURANCE COMPANY USE		
BUILDING OWNER'S NAME	DEGGO	LICY NUMBER	
JIM PETTINATO	IUF		
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER		MPANY NAIC NUMBER	
5362 SANDHAMN PLACE	IIII PROG		
OTHER DESCRIPTION (Lot and Block Numbers, etc.)		DIDTMENT	
LOT 7, SANDHAMN SUBDIVISION	BUILDING	ONGBOAT KEY	
CITY	STATE	ZIP CODE	
LONGBOAT KEY	FL.	34228	
SECTION B. ELOOD INSUBANCE BATE MAD (EIDM)	INFORMATION		

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION
125126	0005	D	MAY 18, 1992	A 13	(in AO Zones, use depth)

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate

the community's BFE:

SECTION C BUILDING ELEVATION INFORMATION

- T. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level <u>1</u>.
 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of <u>1111.0</u> feet NGVD (or other FIRM datum-see Section B, Item 7).
 - (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from

the selected diagram, is at an elevation of LLLL feet NGVD (or other FIRM datum-see Section B, Item 7).

- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is _____. feet above ____ or
 - below \Box (check one) the highest grade adjacent to the building.
- (d) FIRM Zone AO. The floor used as the reference level from the selected diagram is _____. ____ feet above ______ or below _____ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? _____ Yes ____ No _____ Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: X Yes No (See Instructions on Page 4)
- 5. The reference level elevation is based on: 🛛 actual construction 🗌 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)

SECTION D COMMUNITY INFORMATION

If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: https://www.community.com floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: https://www.community.com floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: https://www.community.com floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: https://www.com/www.com floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: <a href="https://www.com"/www.com"/www.com"/www.com"/www.com floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: <a href="https://www.com"/www.com"/www.com"/www.com"/www.com"/www.com floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: <a href="https://www.com"/www.com"/www.com"/www.com"/www.com floodplain management ordinance, the elevation of the building's "lowest floodplain"/www.com floodplain the community of the building of the buildi

FEMA Form 81-31, MAY 93

REPLACES ALL PREVIOUS EDITIONS Scanned to lasurpicker

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal)				
F. PETER LUTZ, JR.	5506				
TILE	COMPANY NAME				
TTLE PROFESSIONAL SURVEYOR	BISHOP. C	Assoc.			
ADDRESS	CITY		STATE	ZIP	
78 SARASOTA CENTER BLVD.	SARASOTA	1	FL.	34240	
SIGNATURE J. Petr hut h.		DATE 7/31/97	PHONE (941) 371-6		
Copies should be made of this Certificate for:	1) community official,	2) insurance ag	ent/company, and 3) build	ling owner.	
COMMENTS:					
CONCRETE SLAB ONLY.					
CONCRETE SLAB ONLY. THE GARAGE ELEV. = 8.8	۲′				
		<u>t</u>			
			1		
Sec 🥠		÷		111	
			1011 B. 28 10	660	
		1.4	SA. it	·	
ON SLAB	WITH BASEMENT		PIEDS, OR COLUMNS	3 6: 6:	
			T.E B		
A V ZONES ZONES	TT ZONES		ZONES ZONES	5-0-2-3	
		1	REFERENCE	14:33	
		BASE	LEVEL	LEVEL	
	2000	ELEVATION		T CON	
	uning further	metur	merina	Sugar	
	-71		Province and	BASE	
BASE		REFERENCE		FLOOD	
ELEVATION REFERENCE ADJACENT	GRADE	LEVEL		N CLEVANON	
			1)// J	Villen I.	
LEVEL GRADE	100 (10) (100 (100 (100 (100 (10) (10) (
				ADJACENT	

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.