O.M.B. No 3067-0077 Expires May 31, 1993

ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

determine the proper insura	n necessary to ensuince premium rate, a	re compliance nd/or to suppor	with applicable communit	y floodplain mar Map Amendme	nt or Revision (LOMA or LOMB
	SECTION A PR			INA	FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME Weston Pointe	, Inc.	n an	1	NI E	POLICY NUMBER
STREET ADDRESS (Including Apt 63 Weston Pointe OTHER DESCRIPTION (Lot and B Lot #2 Weston CITY Town of Longb	Court lock Numbers, etc.) Pointe loat Key	india india a Company	ROUTE AND BOX NUMBER	MAR 30	21P CODE
Provide the following from the	C			INFORMATION	
	2 PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
125126	0010	В	05-18-92	A13	EL 11
. Indicate the elevation datu		the contract of the second		and the second se	

SECTION C BUILDING ELEVATION INFORMATION

 The top of the reference level floor from the selected diagram is at an elevation latum-see Section B, Item 7). be bottom of the lowest horizontal structural member of the reference level from feet NGVD (or other FIRM datum-see Section B, Item 7). the reference level from the selected diagram is 	(b). FIRM Zones V1-V30, VE, and the selected diagram, is at an e
e level from the selected diagram is feet above or below (check If no flood depth number is available, is the building's lowest floor (reference y's floodplain management ordinance? Yes No Unknown mining the above reference level elevations: XX NGVD '29 Other (describe ation datum used in measuring the elevations is different than that used on e elevations to the datum system used on the FIRM and show the conversion Yes XXNo (See Instructions on Page 4) nal construction construction drawings if the building does not yet have the reference level floor in place, in which a during the course of construction. A post-construction Elevation Certificate	 one) the highest grade adjacen level) elevated in accordance w Indicate the elevation datum system under Comments on Page 2). (Not the FIRM [see Section B, Item 7] equation under Comments on Page Elevation reference mark used app The reference level elevation is baa (NOTE: Use of construction draw)
cent to the building is: 09.5 feet NGVD (or other FIRM datum-see	5. The elevation of the lowest grade i Section B, Item 7).
ON D COMMUNITY INFORMATION	
If no flood depth number is available, is the building's lowest floor (reference y's floodplain management ordinance? Yes No Unknown ining the above reference level elevations: XNGVD '29 Other (describe the datum used in measuring the elevations is different than that used on e elevations to the datum system used on the FIRM and show the conversion Yes XNo (See Instructions on Page 4) all construction construction drawings if the building does not yet have the reference level floor in place, in which a during the course of construction. A post-construction Elevation Certificate	 one) the highest grade adjacen level) elevated in accordance w Indicate the elevation datum system under Comments on Page 2). (Not the FIRM [see Section B, Item 7] equation under Comments on Page 4. Elevation reference mark used appendix of the section reference level elevation is back (NOTE: Use of construction drawn case this certificate will only be value will be required once construction in Section B, Item 7). If community official responsible

floor" as defined by the ordinance is:

Date of the start of construction or substantial improvement

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 100 k

10.01	Ber A Star	
CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seahler	General de
John C. Minder, PLS	LS 4071	18 8 4 m
TITLE	COMPANY NAME	Print Print
President	Minder & Rhodes Engineering Corporation	
ADDRESS	CITY	ZIP
3900 Clark Road, Ste H-3	Sarasota 3	4233
SIGNATURE MANCMUSCE	DATE PHONE March 29, 1994 (813)922-7848	
Contraction of the second seco		61

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

. .

COMMENTS:

ON WITH ON PILES, SLAB BASEMENT PIERS, OR COLUMNS V V ZONES ZONES ZONES ZONES ZONES REFERENCE REFERENCE REFERENCE LEVEL BASE LEVEL LEVEL FLOOD ELEVATION BASE BASE FLOOD ELEVATION REFERENCE ADJACENT ELEVATION GRADE LEVEL REFERENCE ADJACENT LEVEL GRADE ADJACENT GRADE

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.