ZIP CODE

ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

FENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to ovide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR INSURANCE COMPANY USE		
BUILDING OWNER'S NAME	POLICY NUMBER		
HUNT BUILDING CORP.			
STREET ADDRESS (Including Apt., Unit, Suite and or Bldg, Number) OR P.O. ROUTE AND BOX NUMBER	COMPANY NAIC NUMBER		
800 + 802 EVERGREEN PL.			
OTHER DESCRIPTION (Lot and Block Numbers. etc.)			

BLDG 32, CEDARS EAST, SECTION III

-	

LONGBOAT KEY

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

STATE

FL

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	8 BASE FLOOD ELEVATION (in AO Zones, use depth)
125126	0005	С	10/01/83	A 13	10

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): XNGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: ______ feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION C BUILDING ELEVATION INFORMATION

Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level _8

- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 11171.2 feet NGVD (or other FIRM datum-see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of ______ feet NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is ______ feet above ____ or below (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is _____ feet above __ or below __ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? ____ Yes ___ No ___ Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: ___ Yes X No (See Instructions on Page 4)
- 5. The reference level elevation is based on: X actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: 1 7 .5 feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest

floor" as defined by the ordinance is: ______ feet NGVD (or other FIRM datum-see Section B, Item 7). Date of the start of construction or substantial improvement ______ 4-24-91___.

2. Date of the start of construction or substantial improvement

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LIC	ENSE NUMBER (or Affix S	eal)		
JAMES N. GATCH, JR.		4295			
TITLE	COMPANY NAME				
ASSISTANT DIRECTOR OF SURVEYING	ZOLLER, NAJ	JAR & SHROYER			
ADDRESS STATE THE STATE	CITY			STATE	ZIP
P.O. BOX 9448	BRADENTON			FL	34206
SIGNATURE Jame N. Gatel J		DATE 4/24/91	рноле (813)	748-8080	
Copies should be made of this Certificate for: 1) co	mmunity official, 2)	insurance agent/co	mpany, and	l 3) building o	wner.
				- 1	
COMMENTS					
			5		
Ł					
				1. gailt	
¥		a ²			
	WITH		ON PILE		- 275-30 - 1
SLAB	BASEMENT		PIERS, OR CO	LUMNS	16 a 1 - 17 a
A V	A		A ZONES	ZONES TAT	at the part
ZONES ZONES	ZONES		_	ZONES W	11. July 10. 1
		AEFERENC	1 m	REFE	RENCE
REFERENCE IV		BASE FLOOD LEVATION			VEL
un and a start where we want we want where we want where we want was a start with the start we want we	my from	uluu .		million	f ~
			NU I		ASE
BASE ADJ		ERENCE			ATION
ELEVATION REFERENCE ADJACENT GRADE			6111	hl	1.161.5
2.	the second second	· · · · · ·	- MIN	A/X	
6	CONTRACTOR OF	1.65	AN AND AND AND		damage 1

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.