U.S. DEPARTMENT OF HOMELAND SECURITY

ELEVATION CERTIFICATE

OMB No. 1660-0008 Expires March 31, 2012

Federal Emergency Management Agency National Flood Insurance Program

Important: Read the instructions on pages 1-9

24	Tigor modification in		mportant.	redu the h	50 400015 011	pages 1-5.	
				ON A - PRO	PERTY INFOR	MATION	For Insurance Company Use:
A1. E	A1. Building Owner's Name David and Julie Fried					Policy Number	
2. E	2. Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. 2741 Gulf of Mexico Drive					Company NAIC Number	
	City Longboat Key	State FL Z	IP Code 34228				
A3. F	Property Description (Lerty ID # 0005- 17-000	_ot and Block Nւ 1	ımbers, Tax Parcel Nu	mber, Legal D	escription, etc.)		
A5. L A6. A A7. E A8. F a b	A4. Building Use (e.g., Residential, Non-Residential, Addition, Accessory, etc.) Residential A5. Latitude/Longitude: Lat. 27 22'02" N Long. 82 37'37" W Horizontal Datum: NAD 1927 NAD 1983 A6. Attach at least 2 photographs of the building if the Certificate is being used to obtain flood insurance. A7. Building Diagram Number 6 A8. For a building with a crawlspace or enclosure(s): a) Square footage of crawlspace or enclosure(s) b) No. of permanent flood openings in the crawlspace or enclosure(s) within 1.0 foot above adjacent grade c) Total net area of flood openings? NAS. Sq in d) Engineered flood openings? NYS Sq No Horizontal Datum: NAD 1927 NAD 1983 A9. For a building with an attached garage: a) Square footage of attached garage within 1.0 foot above adjacent grade within 1.0 foot above adjacent grade N/A sq in b) No. of permanent flood openings in the attached garage within 1.0 foot above adjacent grade N/A sq in c) Total net area of flood openings? No						
			TION B - FLOOD IN	SURANCE	RATE MAP (FI	RM) INFORMATIO	N
Towr	FIP Community Name of Longboat Key		1	2. County Nar Sarasota			B3. State FL
	Map/Panel Number 25126 0010	B5. Suffix B	B6. FIRM Index Date 05/18/92	Effective	FIRM Panel e/Revised Date 8/15/83	B8. Flood Zone(s) V17	B9. Base Flood Elevation(s) (Zone AO, use base flood depth)
B10. Ir			Elevation (BFE) data or	base flood de	epth entered in Ite	em B9.	•
	☐ FIS Profile		Community Determ		Other (Descri	/	
B12. Is	B11. Indicate elevation datum used for BFE in Item B9: NGVD 1929 NAVD 1988 Other (Describe) B12. Is the building located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA)? Yes No Designation Date OPA						
		SECTIO	N C - BUILDING EL	EVATION II	NFORMATION	(SURVEY REQUIF	RED)
A C2. Ele bel Be	C1. Building elevations are based on: ☐ Construction Drawings ☐ Building Under Construction* ☐ Finished Construction *A new Elevation Certificate will be required when construction of the building is complete. C2. Elevations – Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, AR/AO. Complete Items C2.a-h below according to the building diagram specified in Item A7. Use the same datum as the BFE. Benchmark Utilized FDEP MONUMENT A-O5 EL. = 6.12 Vertical Datum NGVD 1929 Conversion/Comments						
	_					Check the measure	ment used.
a) b)	Top of bottom floor Top of the next high		nent, crawlspace, or er	nclosure floor)	21.5		meters (Puerto Rico only)
c)			ctural member (V Zone	es only)	20.2		meters (Puerto Rico only) meters (Puerto Rico only)
d)	Attached garage (to	p of slab)			10.1		meters (Puerto Rico only)
e)	Lowest elevation of (Describe type of ed	machinery or equipment and loc	uipment servicing the cation in Comments)	building A/C	20.3	P feet _ U	meters (Puerto Rico only)
f)	Lowest adjacent (fin				9.5	feet APR	meters (Puerto Rico only)
g) h)			ext to building (HAG) vation of deck or stairs	s, including	9 9	⊠ feet □	meters (Puerto Rico only) meters (Puerto Rico only)
SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION							
This certification is to be signed and sealed by a land surveyor, engineer, or architect authorized by law to certify elevation information. I certify that the information on this Certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001. Check here if comments are provided on back of form. Were latitude and longitude in Section A provided by a licensed land surveyor? Yes No							
Certifie	Certifier's Name Robert G. Bruce License Number 4519						
-itle O			Company Name Rec				TE OF
	Address 7123 Proctor Road City Sarasota Sarasota State FL ZIP Code 34241					Act Labor	
Signatu	re Boletin	Bru	Date 03/	11/2011	Telephone (941) 923 - 9997	- Control

IMPORTANT: In these spaces, or	copy the corresponding information from Sect	ion A. Fo	r Insurance Company Use:
	, Unit, Suite, and/or Bldg. No.) or P.O. Route and Box N		olicy Number
City Longboat Key	State FL ZIP Code 34228	Co	ompany NAIC Number
SECTION	D - SURVEYOR, ENGINEER, OR ARCHITECT	CERTIFICATION (CONTIN	IUED)
	ficate for (1) community official, (2) insurance agent/com		
	e rate map (FIRM) information to be verified at local F.E		
Signature Boleti Sibility	Date 03/11/		☐ Check here if attachments
SECTION E - BUILDING ELE	VATION INFORMATION (SURVEY NOT REQUIR	RED) FOR ZONE AO AND	ZONE A (WITHOUT BFE)
and C. For Items E1-E4, use natural E1. Provide elevation information for grade (HAG) and the lowest adjanal Top of bottom floor (including b) Top of bottom floor (including E2. For Building Diagrams 6-9 with (elevation C2.b in the diagrams)	basement, crawlspace, or enclosure) isbasement, crawlspace, or enclosure) isbermanent flood openings provided in Section A Items 8 of the building is feet meters	whether the elevation is above feet meters abo feet meters abo and/or 9 (see pages 8-9 of Ins above or below the HAI	e or below the highest adjacent ve or below the HAG. ve or below the LAG. structions), the next higher floor
	d/or equipment servicing the building is [☐ feet ☐ meters ☐ above o	
	number is available, is the top of the bottom floor eleval Unknown. The local official must certify this informati		nmunity's floodplain management
	F - PROPERTY OWNER (OR OWNER'S REPR		TION
	zed representative who completes Sections A, B, and E		ssued or community-issued BFE)
Property Owner's or Owner's Authoriz	ed Representative's Name		
^ dress	City	State	ZIP Code
Signature	Date	Telephone	
Comments			
			Charle have if attachmen
	SECTION G - COMMUNITY INFORMATIO	ON (OPTIONAL)	Check here if attachmen
	w or ordinance to administer the community's floodplain plete the applicable item(s) and sign below. Check the	management ordinance can o	
is authorized by law to certify G2. A community official complete	was taken from other documentation that has been signelevation information. (Indicate the source and date of additional decision of the source and date of a section E for a building located in Zone A (without a Formal decision of the source and section E for a building located in Zone A (without a Formal decision).	the elevation data in the Comn FEMA-issued or community-iss	nents area below.)
	ms G4-G9) is provided for community floodplain manage		
G4. Permit Number	G5. Date Permit Issued G6.	Date Certificate Of Complian	ce/Occupancy Issued
G9. BFE or (in Zone AO) depth of floor G10. Community's design flood elevation	ding at the building site:	eet	APR 2 0 2011 N OF LONGBOAT KEY
Local Official's Name	Title	Plant	ning, Zoning and Building
Community Name	Telephon	е	
Signature	Date		
nments	:		
			Check here if attachmen

Building Photographs See Instructions for Item A6.

			For Insurance Company Use:
Building Street Address (including	Policy Number		
2741 Gulf of Mexico Drive			
City Longboat Key	State FL	ZIP Code 34228	Company NAIC Number
	· -	0.1220	

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least two building photographs below according to the instructions for Item A6. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." If submitting more photographs than will fit on this page, use the Continuation Page, following.



Front View

Rear View



APR 2 0 2011

TOWN OF LONGBOAT KEY Planning, Zoning and Building

Building Photographs

See Instructions for Item A6.

					For Insurance Company Use:
J ailding	Street Addres	s (including Apt., Uni	t, Suite, and/or Bldg. No.)	or P.O. Route and Box No.	Policy Number
City	State	ZIP Code			Company NAIC Number
If using the Elevation Cartificate to obtain NEID flood incurrence office at least two building photographs below according to					

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least two building photographs below according to the instructions for Item A6. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." If submitting more photographs than will fit on this page, use the Continuation Page, following.

FRONT VIEW "SEE ATTACHED"



Building Photographs Continuation Page

		•	For Insurance Company Use:
Puilding S	Street Addres	s (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No.	Policy Number
City	State	ZIP Code	Company NAIC Number
8			

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View."

REAR VIEW
"SEE ATTACHED"





This report is subject to re-examination in one year.

ICC Evaluation Service, Inc.

www.icc-es.org

Business/Regional Office ■ 5360 Workman Mill Road, Whittier, California 90601 ■ (562) 699-0543

Regional Office ■ 900 Montclair Road, Suite A, Birmingham, Alabama 35213 ■ (205) 599-9800

Regional Office ■ 4051 West Flossmoor Road, Country Club Hills, Illinois 60478 ■ (708) 799-2305

DIVISION: 10—SPECIALTIES Section: 10230—Vents

REPORT HOLDER:

SMART VENT®, INC.
450 ANDBRO DRIVE, SUITE 2B
PITMAN, NEW JERSEY 08071
877-441-8368
www.smartvent.com
eval@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: FLOODVENT™ MODEL #1540-520; FLOODVENT™ STACKING MODEL #1540-521; SMARTVENT™ MODEL #1540-510; SMARTVENT™ STACKING MODEL #1540-511; WOOD WALL FLOOD MODEL #1540-570; WOOD WALL FLOOD OVERHEAD DOOR MODEL #1540-574; FLOODVENT™ OVERHEAD DOOR MODEL #1540-524; SMARTVENT™ OVERHEAD DOOR MODEL #1540-514

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code® (IBC)
- 2006 International Residential Code® (IRC)

Properties evaluated:

- Physical operation
- Water flow

2.0 USES

The Smart Vent® units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

3.0 DESCRIPTION

3.1 General:

When subjected to pressure from rising water, the Smart Vent® AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to unlatch, allowing the plate to rotate out of the way and allow flow. The water

level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 76 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

3.4 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

4.0 INSTALLATION

SmartVENT® and FloodVENT™ are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and concrete walls up to 12 inches (305 mm) thick. In order to comply with the engineered opening design principle noted in Section 2.6.2.2 of ASCE/SEI 24, the Smart Vent® AFFVs must be installed as follows:

- With a minimum of two openings on different sides of each enclosed area
- With a minimum of one AFFV for every 200 square feet (18.6 m²) of enclosed area, except that the SmartVENT™

REPORTS are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, Inc., express or implied, as to any finding or other matter in this report, or as to any product covered by the report.



Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 must be installed with a minimum of one AFFV for every 400 square feet (37.2 m²) of enclosed area.

- Below the base flood elevation
- With the bottom of the AFFV located a maximum of 12 inches (305.4 mm) above grade.

5.0 CONDITIONS OF USE

The Smart Vent® AFFVs described in this report comply with, or are suitable alternatives to what is specified in, those codes listed in Section 1.0 of this report, subject to the following conditions:

5.1 The Smart Vent[®] AFFVs must be installed in accordance with this report, the applicable code and the manufacturer's installation instructions. In the event of a conflict, the instructions in this report govern.

5.2 The Smart Vent® AFFVs must not be used in the place of "breakaway walls" in coastal high hazard areas, but are permitted for use in conjunction with breakaway walls in other areas.

6.0 EVIDENCE SUBMITTED

Data in accordance with the ICC-ES Acceptance Criteria for Automatic Foundation Flood Vents (AC364), dated October 2007.

7.0 IDENTIFICATION

The Smart VENT®, models recognized in this report must be identified by a label bearing the manufacturer's name (Smart Vent, Inc.), the model number, and the evaluation report number (ESR-2074).