#### U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY

National Flood Insurance Program

# **ELEVATION CERTIFICATE**

IMPORTANT: Follow the instructions on pages 1-9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

					FOR INSURANCE COMPANY USE	
A1. Building Owner's Name Diana Ruth Harmas					Policy Number:	
607 Inton Bend				Company NAI		
City Longboat Key			ate FI	2	ZIP Code 34	228
A3. Property Description (Lot and Block Numbers, Tax P. Lot 2, Collier-Walker PB 46, PG 26, Sarasota	arcel Numbe County	r, Legal Descript	ion, etc.)			
<ol> <li>Building Use (e.g., Residential, Non-Residential, Add</li> <li>Latitude/Longitude: Lat. N27°22'17 5"</li> </ol>						
A5. Latitude/Longitude: Lat. N27°22'17.5"  A6. Attach at least 2 photographs of the building if the (		. W82°37'41.4 being used to o		Horizontal I urance.	Datum: 🔲 N	NAD 1927 🗷 NAD 1983
A7. Building Diagram Number 1B						
<ul><li>A8. For a building with a crawlspace or enclosure(s):</li><li>a) Square footage of crawlspace or enclosure(s)</li></ul>	N/	Asqft		uilding with an att		621
Number of permanent flood openings in the craw or enclosure(s) within 1.0 foot above adjacent gr	Ispace	3q it	b) Nun	are footage of att ober of permanen in 1.0 foot above	t flood openi	ngs in the attached garage
c) Total net area of flood openings in A8.b	N/A	A sq in		I net area of floor		
d) Engineered flood openings? ☐ Yes ☒ No			d) Eng	ineered flood ope	enings?	¶Yes □ No
SECTION B - FL  B1. NFIP Community Name & Community Number	OOD INSU			) INFORMATIO	N	
Longboat Key Fl 125126		B2. County Nar Sarasota	ne			B3. State Florida
B4. Map/Panel Number B5. Suffix B6. FIRM Inc.	lex Date	B7. FIRM Panel Revised Da		B8. Flood Zone(s		e Flood Elevation(s) (Zone
125126 0010 B 05/18/	1992	08/15/1		A13	AO, I	use base flood depth) 11
B10. Indicate the source of the Base Flood Elevation (BFE ☐ FIS Profile ☐ FIRM ☐ Community Determin		se flood depth er	ntered in Item	B9:		
B11. Indicate elevation datum used for BFE in Item B9:	<b>⊠</b> NGVD	1929 □ NA		Other/Source:		
B12.Is the building located in a Coastal Barrier Resource			erwise Protect	ted Area (OPA)?	Yes	<b>⊠</b> No
Designation Date: / / C		] OPA				
SECTION C - BUILD	SECTION C - BUILDING ELEVATION INFORMATION (SURVEY REQUIRED)					
Building elevations are based on: Construction Drawings* Building Under Construction*  *A new Elevation Certificate will be required when construction of the building is complete.						
C2. Elevations - Zones A1-A30, AE, AH, A (with BFE), VE,	C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, AR/A0. Complete Items C2.a–h below according to the building diagram specified in Item A7. In Puerto Rico only, enter meters.					mplete Items
Benchmark Utilized: RM6	ified in Item			meters.		
Indicate elevation datum used for the elevations in items a) through h) below.   NGVD 1929  NAVD 1988  Other/Source:					urce:	
Datum used for building elevations must be the same			10 0	Check the me	asurement u	used.
<ul> <li>a) Top of bottom floor (including basement, crawlspant)</li> <li>b) Top of the next higher floor</li> </ul>	ce, or enclos	ure floor)	12 . 3	_ ⊠ feet	meters	
c) Bottom of the lowest horizontal structural member	// Zones or		N/A	_ ⊠ feet	meters	
d) Attached garage (top of slab)	(V Zuries ur	iiy)	8 4	_ ☐ feet	meters	
e) Lowest elevation of machinery or equipment service	ing the build	ding	14 . 5	_ ⊠ feet _ ⊠ feet	meters	
(Describe type of equipment and location in Comm f) Lowest adjacent (finished) grade next to building (I			0 2			
g) Highest adjacent (finished) grade next to building (		-	<u>8</u> . <u>3</u> 9.1	_ Ifeet	meters	
h) Lowest adjacent grade at lowest elevation of deck		cluding	9.0	_ ⊠ feet _ ⊠ feet	☐ meters	
structural support	,			_ 21000	LI meters	
SECTION D - SUR	VEYOR, EN	GINEER, OR	ARCHITECT	CERTIFICATIO	N	
his certification is to be signed and sealed by a land survey of a land survey of formation. I certify that the information on this Certificate re	yor, engineer	or architect aut	horized by law	to certify elevation		ROBER
understand that any false statement may be punishable by to Check here if comments are provided on back of form.					- 2h	RTIFIGATIKA
Check here if attachments.	licensed	ude and longitud land surveyor?	CONTRACT CO.	No No	= 40	10 4661 E
Certifier's Name KENNETH R. PALMER			License Numb	per	= 0 10	, signetel : + E
SURVEYOR		Name R LAND SUR		2	- FG	STATE OF 15:05
5 TALLEVAST ROAD	City SARAS	ОТА	State FL	ZIP Code 34243	10/4	CORIU
refrature for the form	Date 10/22/2	014	Telephone (941) 527-0		17/	ED LAND S

## **ELEVATION CERTIFICATE**, page 2

IMPORTANT: In these spaces con	y the corresponding information from Sec	tion A	L FOR INCURANCE	201/2111///05
	Apt., Unit, Suite, and/or Bldg. No.) or P.O. Ro		FOR INSURANCE (	COMPANY USE
607 Triton Bend	ipt., offit, Suite, and/or blog. No.) or no. At	oute and Box No.	Policy Number:	
ongboat Key	State FI	ZIP Code 34228	Company NAIC Numb	ber:
SECTI	ON D - SURVEYOR, ENGINEER, OR	ARCHITECT C	ERTIFICATION (CONTINUED)	
	ertificate for (1) community official, (2) insu			
Comments 350-004A Building is	stem wall construction. C2.e) Air con	ditioner unit on	right side of building.	
	,			
Signature	$\sqrt{A/D}$	Date 10/22/	2014	
SECTION F - BUILDING F	LEVATION INFORMATION (SURVEY			WITHOUT BEEN
	omplete Items E1–E5. If the Certificate is i	NAME AND ADDRESS OF THE OWNER, WHEN PERSON NAMED IN		
For Items E1–E4, use natural grade,	if available. Check the measurement used	l. In Puerto Rico	only, enter meters.	
<ol> <li>Provide elevation information for grade (HAG) and the lowest adja</li> </ol>	r the following and check the appropriate bocent grade (LAG).	oxes to show who	ther the elevation is above or below the	highest adjacent
a) Top of bottom floor (including	basement, crawlspace, or enclosure) is		☐ feet ☐ meters ☐ above or [	below the HAG.
b) Top of bottom floor (including	basement, crawlspace, or enclosure) is		☐ feet ☐ meters ☐ above or ☐	below the LAG.
	permanent flood openings provided in Sect	ion A Items 8 and	I/or 9 (see pages 8–9 of Instructions),	
	2.b in the diagrams) of the building is			below the HAG.
3. Attached garage (top of slab) is				below the HAG.
	d/or equipment servicing the building is			below the HAG.
.s. Zone AO only: If no flood depth r ordinance? ☐ Yes ☐ No ☐	number is available, is the top of the bottor Unknown. The local official must certify the	n floor elevated in his information in	accordance with the community's flood Section G.	plain management
SECTIO	ON F - PROPERTY OWNER (OR OW	NER'S REPRES	SENTATIVE) CERTIFICATION	National Association and Control of Control
he property owner or owner's autho	rized representative who completes Section	ns A, B, and E for	Zone A (without a FEMA-issued or comp	nunity-issued BFE) of
Cone AO must sign here. The statem Property Owner or Owner's Authorize	nents in Sections A, B, and E are correct to d Representative's Name	the best of my k	iowledge.	
dress		City	State ZIP Cod	le
Signature		Date	Telephone	
Comments				
			Check h	ere if attachments.
	SECTION G - COMMUNITY			
he local official who is authorized by of this Elevation Certificate. Comple	law or ordinance to administer the communi te the applicable item(s) and sign below. Ch	ity's floodplain ma	nagement ordinance can complete Section nent used in Items G8–G10. In Puerto Ric	ns A, B, C (or E), and
1. The information in Section (	C was taken from other documentation that	at has been sign	ed and sealed by a licensed surveyor or	ndinner er erebitee
who is authorized by law to	certify elevation information. (Indicate the	source and date	of the elevation data in the Comments	area below.)
<ol> <li>The following information (It</li> </ol>	ted Section E for a building located in Zone tems G4–G10) is provided for community f	e A (without a FEN floodplain manag	A-issued or community-issued BFE) or Zi ement purposes.	one AO.
4. Permit Number	G5. Date Permit Issued	G6.	Date Certificate Of Compliance/Occupan	ncy Issued
7. This permit has been issued for	: New Construction Substanti	al Improvement		
	(including basement) of the building:		☐ feet ☐ meters Datum	
<ol><li>BFE or (in Zone AO) depth of floor</li></ol>			☐ feet ☐ meters Datum	
10. Community's design flood elevat	ion:		feet meters Datum	
ocal Official's Name		Title		
ommunity Name		Telephone		
gnature		Date		
omments				
			Check he	ere if attachments

# **ELEVATION CERTIFICATE**, page 4

## **BUILDING PHOTOGRAPHS**

Continuation Page

	MPORTANT: In these spaces, copy the corresponding information from Section A.  FOR INSURANCE COMPANY USE				
PRODUCTO SPECIFICATION OF THE PERSON OF THE	Building Street Address (including Apt., Unit, S 607 Triton Bend	Policy Number:			
T	ity Longboat Key	State FI	ZIP Code 34228	Company NAIC Number:	

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8.





# **ELEVATION CERTIFICATE**, page 3

## **BUILDING PHOTOGRAPHS**

See Instructions for Item A6.

	IMPORTANT: In these spaces, copy the corresponding	ese spaces, copy the corresponding information from Section A. FOR INSURANCE COMPANY USE			
	Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or PO. Route and Box No. 607 Triton Bend			Policy Number:	
4	ity Longboat Key	State FI	ZIP Code 34228		Company NAIC Number:

If using the Elevation Certificate to obtain NFIP flood insurance, affix at least 2 building photographs below according to the instructions for Item A6. Identify all photographs with date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View." When applicable, photographs must show the foundation with representative examples of the flood openings or vents, as indicated in Section A8. If submitting more photographs than will fit on this page, use the Continuation Page.

FRONT VIEW





# **ICC-ES Evaluation Report**

ESR-2074\*

Reissued December 1, 2012

This report is subject to renewal February 1, 2015.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00—OPENINGS Section: 08 95 43—Vents/Foundation Flood Vents

#### REPORT HOLDER:

SMARTVENT PRODUCTS, INC. 430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071 (877) 441-8368 www.smartvent.com

www.smartvent.com info@smartvent.com

### **EVALUATION SUBJECT:**

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: FLOODVENT™ MODEL #1540-520; FLOODVENT™ STACKING MODEL #1540-521; SMARTVENT™ MODEL #1540-510; SMARTVENT™ STACKING MODEL #1540-511; WOOD WALL FLOOD MODEL #1540-570; WOOD WALL FLOOD OVERHEAD DOOR MODEL #1540-524; SMARTVENT™ OVERHEAD DOOR MODEL #1540-514

#### 1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2009 and 2006 International Building Code® (IBC)
- 2009 and 2006 International Residential Code® (IRC)

#### Properties evaluated:

- Physical operation
- Water flow

## **2.0 USES**

The Smart Vent® units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. The Smart Vent® units are intended for use where flood hazard areas have been established in accordance with IBC Section 1612.3 or IRC Section R3222.1. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

#### 3.0 DESCRIPTION

### 3.1 General:

When subjected to pressure from rising water, the Smart Vent® AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic

pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit.

#### 3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

#### 3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ Inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-570 units measure 14 inches wide by 8³/₄ Inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

## 3.4 Ventilation:


The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square Inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

### 4.0 INSTALLATION

SmartVENT® and FloodVENT™ are designed to be installed into walls or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and

\*Revised July 2013







# **ICC-ES Evaluation Report**

# ESR-2074 FBC Supplement

Issued July 1, 2013

This report is subject to renewal February 1, 2015.

www.icc-es.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 08 00 00-OPENINGS

Section: 08 95 43-Vents/Foundation Flood Vents

REPORT HOLDER:

SMARTVENT PRODUCTS, INC. 430 ANDBRO DRIVE, UNIT 1 PITMAN, NEW JERSEY 08071 (877) 441-8368 www.smartvent.com info@smartvent.com

### **EVALUATION SUBJECT:**

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS: FLOODVENT™ MODEL #1540-520; FLOODVENT™ STACKING MODEL #1540-521; SMARTVENT™ MODEL #1540-510; SMARTVENT™ STACKING MODEL #1540-511; WOOD WALL FLOOD WODEL #1540-570; WOOD WALL FLOOD OVERHEAD DOOR MODEL #1540-574; FLOODVENT™ OVERHEAD DOOR MODEL #1540-514

### 1.0 REPORT PURPOSE AND SCOPE

#### Purpose:

The purpose of this evaluation report supplement is to indicate that Smart Vent® Automatic Foundation Flood Vents, recognized in ICC-ES master report ESR-2074, have also been evaluated for compliance with the codes noted below.

#### Applicable code editions:

- 2010 Florida Building Code—Building (FBC)
- 2010 Florida Building Code—Residential (FRC)

### 2.0 CONCLUSIONS

The Smart Vent® Automatic Foundation Flood Vents, described in Sections 2.0 through 7.0 of the master evaluation report ESR-2074, comply with the FBC and the FRC, provided the design and installation are in accordance with the *International Building Code®* provisions noted in the master report.

Use of the Smart Vent® Automatic Foundation Flood Vents has also been found to be in compliance with the High-Velocity Hurricane Zone provisions of the FBC and the FRC for structures not subject to FBC Section 2326.3.1 or FRC Section 4409.13.3.1, as applicable.

For products falling under Florida Rule 9N-3, verification that the report holder's quality assurance program is audited by a quality assurance entity approved by the Florida Building Commission for the type of inspections being conducted is the responsibility of an approved validation entity (or the code official when the report holder does not possess an approval by the Commission).

This supplement expires concurrently with the master report, reissued December 1, 2012, revised July 2013.

