

LEGEND

- CHANGE IN PRIORITY BAR PLACEMENT**
- ① FIRST PRIORITY
 - ② SECOND PRIORITY
 - ③ THIRD PRIORITY
- SLAB STEPS AND SLOPES**
(SEE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS)
- ④ 3/4" DAP OUT
 - ⑤ 3/4" STEP AT WALL LINE AND SLOPE SLAB TO EDGE
- SLAB THICKNESS IN INCHES**
(SEE ARCHITECTURAL DRAWINGS FOR SLOPE DETAILS)
- | | | |
|-------|-------|-------|
| 5-1/2 | 6-3/4 | 7-1/2 |
| 6 | 7 | 7-3/4 |
| 6-1/2 | 7-1/4 | 8 |
- SLAB THICKNESSES SHOWN ARE MINIMUM DIMENSIONS.

SLAB NOTES
SLAB THICKNESS = 8" (EXCEPT WHERE NOTED ON TOP STEEL SHT.)
CONCRETE STRENGTH = 4000 P.S.I.
REINFORCING STEEL
GRADE = A615-60
PLACEMENT NOTES & DETAILS = SHT. #S-14
(+) BARS ARE ADD BARS & ARE IN ADDITION TO GRID REINF. SHOWN ON PLAN

REFERENCE NOTES
COLUMN SCHEDULE = SHT. #S-15
SHEARWALL SCHEDULE = SHT. #S-16
BEAM SCHEDULE = SHT. #S-17

