

LEGEND

CHANGE IN PRIORITY BAR PLACEMENT

① FIRST PRIORITY
 ② SECOND PRIORITY
 ③ THIRD PRIORITY

SLAB STEPS AND SLOPES
 (SEE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS)

④ 3/4" DAP OUT
 ⑤ 3/4" STEP AT WALL LINE AND SLOPE SLAB TO EDGE

SLAB THICKNESS IN INCHES
 (SEE ARCHITECTURAL DRAWINGS FOR SLOPE DETAILS)

5-1/2	6-3/4	7-1/2
6	7	7-3/4
6-1/2	7-1/4	8

SLAB THICKNESSES SHOWN ARE MINIMUM DIMENSIONS.

SLAB NOTES
 SLAB THICKNESS = 8" (EXCEPT WHERE NOTED ON TOP STEEL SHT.)
 CONCRETE STRENGTH = 4000 PS.I.
 REINFORCING STEEL
 GRADE = A015-00
 PLACEMENT NOTES & DETAILS = SHT. #S-14
 (+) BARS ARE ADD BARS & ARE IN ADDITION TO GRID REINF. SHOWN ON PLAN

REFERENCE NOTES
 COLUMN SCHEDULE = SHT. #S-15
 SHEARWALL SCHEDULE = SHT. #S-16
 BEAM SCHEDULE = SHT. #S-17

