



LEGEND

CHANGE IN PRIORITY BAR PLACEMENT

① FIRST PRIORITY
 ② SECOND PRIORITY
 ③ THIRD PRIORITY

SLAB STEPS AND SLOPES
 (SEE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS)

④ 3/4" DAP OUT
 ⑤ 3/4" STEP @ WALL LINE AND SLOPE SLAB TO EDGE

SLAB THICKNESS IN INCHES
 (SEE ARCHITECTURAL DRAWINGS FOR SLOPE DETAILS)

◇ -1/2	6-3/4	7-1/2
◇ 7	7	7-3/4
◇ 6-1/2	7-1/4	8

SLAB THICKNESSES SHOWN ARE MINIMUM DIMENSIONS.

SLAB NOTES

SLAB THICKNESS = 8" (EXCEPT AS NOTED)
 CONCRETE STRENGTH = 4000 PSI
 REINFORCING STEEL GRADE = A615-60
 PLACEMENT NOTES & DETAILS = SHEET S-14. (+) BARS ARE ADD BARS AND ARE IN ADDITION TO GRID REINF. SHOWN ON PLAN.

REFERENCE NOTES

COLUMN SCHEDULE = SHEET #S-15
 SHEARWALL SCHEDULE = SHEET #S-16
 BEAM SCHEDULE = SHEET #S-17