



LEGEND

CHANGE IN PRIORITY BAR PLACEMENT

① FIRST PRIORITY
 ② SECOND PRIORITY
 ③ THIRD PRIORITY

SLAB STEPS AND SLOPES
 (SEE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS)

④ 1/4" DAP CUT
 ⑤ 1/4" STEPS NAIL LINE AND SLOPE PLAN TO EDGE

SLAB THICKNESS IN INCHES
 (SEE ARCHITECTURAL DRAWINGS FOR SLOPE DETAILS)

◇ 5-1/2	6-3/4	7-1/2
6	7	7-3/4
6-1/2	7-1/4	8

SLAB THICKNESSES SHOWN ARE MINIMUM DIMENSIONS.

SLAB NOTES

SLAB THICKNESS = 8" (EXCEPT AS NOTED)
 CONCRETE STRENGTH = 4000 PSI.
 REINFORCING STEEL GRADE = A615-60
 PLACEMENT NOTES & DETAILS = SHEET S-14. (+) BARS ARE ADD BARS AND ARE IN ADDITION TO GRID REINF. SHOWN ON PLAN.

REFERENCE NOTES

COLUMN SCHEDULE = SHEET #S-15
 SHEARWALL SCHEDULE = SHEET #S-16
 BEAM SCHEDULE = SHEET #S-17

ISSUED	12-10-82
REVISED	1-4-83
	11-11-83